HYVAC PRODUCTS, INC.

Mail: P.O. Box 389 • Phoenixville, Pa • 19460-0389 • U.S.A. Plant: 201 North 5^{TH} Avenue • Royersford, PA • 19468 • U.S.A.

610-792-0500 PHN • 610-792-0600 FAX

EMAIL jeff@hyvac.com

INTERNET HTTP://WWW.HYVAC.COM

MediVac 300 Vacuum Pump



HYVAC MediVac pumps are modern, continuous direct-drive medium vacuum dutv. pumps featuring a clean, functional design that provides high performance with vibrationless operation. They are portable, relatively guiet and essentially pulse free. They are suitable for work to 24-27" of mercury vacuum. They are a good choice for vacuum holding, pick and place type applications, degassing, gas sampling and vacuum frames. They are "oil free" rotary vane pumps and all come with intake and exhaust filters. Cast Iron pump housings, self-lubricating vanes, sealed

bearings all provide for a long service life. Included internal filter and muffler silencer.

97111-001 MediVac 300 has a displacement of 300 Liter per minute (10 CFM). Will go to a vacuum pressure of 26 inches of mercury vacuum. Pump weighs 62 pounds and measures 8.9"H x 6.5"W x 16.2"L. 3/4 HP Motor 110-120V 50/60Hz and 3/8" NPT ports.

Dimensions in Inches

ſ	Model	Α	В	С	D	E	F	G	Н	I	J	K	L
ſ	300	2.00	2.00	6.47	8.88	3'50 ⁻	.16	6.50	4.88	16.20	6.76	3.00	4.00



